



**WESTERN COLLOID**  
**Material Safety Data Sheet**  
**# 302 PARK TOP SEALCOAT**  
**& # 327 (Tight Surface Sealcoat)**

Date: 09/01/11

Chemical Formula: Mixture

**SECTION 1 - MANUFACTURER INFORMATION**

|                               |  |  |
|-------------------------------|--|--|
| <i>Manufacturer's Name:</i>   | Western Colloid S.C., Inc.                         | Western Colloid N.C., Inc.                   |
| <i>Address:</i>               | 654 E. 60 <sup>th</sup> St., Los Angeles, CA 90001 | 700 71 <sup>st</sup> Ave., Oakland, CA 94621 |
| <i>Emergency Phone No.:</i>   | 323-231-8292                                       | 510-430-0270                                 |
| <i>Information Phone No.:</i> | 323-231-8292                                       | 510-430-0270                                 |

**SECTION II – HAZARDOUS INGREDIENTS**

| <u>CHEMICAL NAME</u>                   | <u>CAS NUMBER</u> | <u>WT. PERCENT</u> | <u>TLV</u>         |
|--|-------------------|--------------------|--------------------|
| SILICEOUS MATERIAL (clay & sand)       | 14808-60-7        | <34%               | N/A                |
| ASPHALT (TLV is for fumes when heated) | 8052-42-4         | <24%               | 5mg/m <sup>3</sup> |
| WATER                                  | 732-18-5          | <40%               | NDA                |
| Carbon Black                           | 133-86-4          | <2%                | NDA                |

**SECTION III – PHYSICAL DATA**

APPEARANCE: BLACKISH/BROWN, VISCOUS LIQUID.  
ODOR: MILD ASPHALTIC ODOR

|   |  |
|---|--|
| BOILING POINT: SAME AS WATER (H <sub>2</sub> O)         | EVAPORATION RATE (BUTYL ACETATE=1): NONE |
| VAPOR PRESSURE (mmHG): 17                               | SPECIFIC GRAVITY (Water=1): 1.32         |
| WATER SOLUBILITY: DISSOLVES IN WATER                    | MELTING POINT: N/A                       |
| VAPOR DENSITY (Air=1): SAME AS WATER (H <sub>2</sub> O) |  |

**SECTION IV – FIRE AND EXPLOSION HAZARD DATA**

FLAMMABLE LIMITS: N/A  
FLASH POINT: NONE  
EXTINGUISHING METHOD: WATER (H<sub>2</sub>O), CO<sub>2</sub>, OR DRY CHEMICAL  
UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE

SPECIAL FIRE-FIGHTING PROCEDURES: NONE

**SECTION V – PHYSICAL HAZARDS (REACTIVITY DATA)**

STABILITY (THERMAL, LIGHT): STABLE  
INCOMPATIBILITY (MATERIAL TO AVOID): NONE KNOWN  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
HAZARDOUS DECOMPOSITION PRODUCTS: N/A

**SECTION VI – HEALTH HAZARDS**

ROUTE(S) OF ENTRY: INHALATION? NO SKIN? NO INGESTION? NO  
HEALTH HAZARDS (ACUTE & CHRONIC): NONE  
CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

SIGNS AND SYMPTOMS OF EXPOSURE: PROLONGED SKIN CONTACT MAY CAUSE DERMATITIS.  
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN

**SECTION VII – EMERGENCY & FIRST AID**

SKIN: WASH WITH SOAP AND CLEAN WATER.  
EYES: FLUSH WITH CLEAN WATER.

## # 302 & #327 PARK TOP SEALCOAT - Page 2

---

### SECTION VIII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: RECOVER SPILLED MATERIAL WITH SCOOP OR SHOVEL. MAY BE REUSED. ALLOW RESIDUE TO DRY.

WASTE DISPOSAL METHOD: DRIED MATERIAL IS NOT A HAZARDOUS WASTE. DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE ABOVE FREEZING.

OTHER PRECAUTIONS: AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

---

### SECTION IX – CONTROL MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): NONE REQUIRED.

VENTILATION:

LOCAL EXHAUST: NONE

SPECIAL: NONE

MECHANICAL (GENERAL): NONE

OTHER: NONE

PROTECTIVE GLOVES: YES

EYE PROTECTION: YES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: NONE

WORK/HYGIENIC PRACTICES: USE GOOD HOUSEKEEPING PRACTICES.

---

### SECTION X - OTHER INFORMATION

|               | Health | Flammability | Reactivity | Personal Protection Index |
|---------------|--------|--------------|------------|---------------------------|
| HMIS* Rating: | 1      | 0            | 0          | 1                         |
| NFPA** Rating | 1      | 0            | 0          |                           |

#### Regulatory Information:

California Proposition 65:

This product contains a chemical(s) known to the State of California to cause cancer or reproductive harm.

(Fumes from asphalt when heated and dust from silica are listed as Prop 65 items. However when used under normal conditions in an aqueous solution exposure to these chemicals is not expected.)

Notice: These ratings involve data and interpretations that may vary from company to company and are intended only for rapid, general identification of the magnitude of the specific hazard. TO DEAL ADEQUATELY WITH THE SAFE HANDLING OF THIS MATERIAL ALL OF THE INFORMATION CONTAINED IN THIS MSDS MUST BE CONSIDERED. The customer is responsible for determining the proper personal protective equipment needed for its particular use of this material.

\* Hazardous Materials Identification Systems [HMIS] Revised RAW MATERIALS RATING MANUAL, National Paint & Coatings Association, Fall 1984.

\*\* NFPA 704 Standard System for the Identification of the Fire Hazards of Materials, National Fire Protection Association, 1985

The information contained herein is furnished without warranty of any kind. Users should consider this data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers. Information on this form is furnished solely for the purpose of compliance with OSHA Hazard Communication Standard, 20 CFR 1910.1200, the Workplace Hazardous Material Information System (WHMIS), and shall not be used for any other purpose.